

Heavy-Duty (Slim) Commercial Grade 1 Surface Applied

DC800 SERIES



FEATURES

- | | |
|-------------------------|--|
| Performance | <ul style="list-style-type: none"> Complies with ANSI A156.4 Grade 1 2 million cycles UL/ULC listed up to 3 hours fire rated |
| Chassis/Closer | <ul style="list-style-type: none"> Cast aluminum |
| Handing | <ul style="list-style-type: none"> Non-handed |
| Mounting | <ul style="list-style-type: none"> Tri-Pack — regular, top jamb and parallel arm applications. |
| Main Arm | <ul style="list-style-type: none"> Stamped steel Accommodates reveals up to 3 1/4" Adjustable extension arm |
| Spring Power | <ul style="list-style-type: none"> Spring power adjustable size 1 - 6 standard for interior and exterior applications |
| Backcheck | <ul style="list-style-type: none"> Adjustable Hydraulic - providing cushioning and preventing uncontrolled openings of the door |
| Valves | <ul style="list-style-type: none"> Adjustable, independent Non-critical (sweep and latch) Consistent closing speeds |
| Fasteners | <ul style="list-style-type: none"> Metal screws included for hollow metal and aluminum mounting applications. Wood screws included for wood door mounting applications. Closers are packed with thru-bolts. |
| Door Range | <ul style="list-style-type: none"> Up to 180 degrees |
| Door Preparation | <ul style="list-style-type: none"> 12" horizontal and 3/4" vertical mounting hole locations (retrofits traditional closer) |
| Cover | <ul style="list-style-type: none"> High impact plastic streamlined cover |
| Warranty | <ul style="list-style-type: none"> Lifetime limited |

DC800 SERIES

OPTIONS

HOLD OPEN ARM Forged steel with hold open adjustable from 80 to 135 degrees

DOOR SIZING

816 Regular and Top Jamb Installation

CLOSER	DOOR TYPE	DOOR WIDTH						
		2' min	2.5' max	3' max	3.5' max	4' max	4.5' max	5' max
816	Interior	✓	✓	♿	✓	✓	✓	✓
	Exterior	✓	✓	♿	✓	✓	✓	N/A

Parallel Arm Installation

CLOSER	DOOR TYPE	DOOR WIDTH						
		2' min	2.5' max	3' max	3.5' max	4' max	4.5' max	5' max
816PA	Interior	✓	✓	♿	✓	✓	✓	N/A
	Exterior	✓	✓	♿	✓	✓	N/A	N/A

✓ = Recommended

N/A = Not applicable or recommended

♿ = Opening force 5 lbs. on interior and 8.5 lbs. on exterior