

Light-Duty Grade 3 Tubular
LT3500 SERIES



Cortland

FEATURES

- Performance**
- Complies with ANSI A156.2, Series 4000, Grade 3
 - Meets ANSI A117.1 American Disabilities Act (ADA) accessibility code
 - Grade 3 light duty
 - 200,000 cycles

- Chassis**
- Tubular
 - Steel - coated with zinc dichromate (corrosion resistance)

- Lever**
- Non-handed, solid cast

- Latch**
- 1" x 2 1/4", square corner faceplate
 - 1" housing diameter (stainless steel)
 - 1/2" throw

- Rose**
- 2 1/2" diameter

- Backset**
- Adjustable 2 3/4" or 2 3/8"

- Strike**
- Standard: 2-3/4" x 1-1/8" standard T-strike
 - Optional strikes available

- Cylinder**
- SCC - C keyway
 - 5-pin solid brass
 - Keyed different (KD)

- Keys**
- Two nickel silver per lock cylinder

- Door Thickness**
- 1 3/8" – 2"

- Door Preparation**
- 2 1/8" diameter
 - 1" diameter for latchbolt
 - Fits standard 161 door prep

- Warranty**
- Lifetime limited

Light-Duty Grade 3 Tubular

LT3500 SERIES

OPTIONS

KEYING OPTIONS Grand master key (GMK), construction master key (CMK), master key (MK), keyed different (KD), keyed alike (KA), interchangeable core uncombined (IC), 0-bitted (OBIT)

TELL FINISHES



US15
Satin Nickel



US26D
Satin Chrome



US19
Matte Black